

Home Assistant

[homeassistant, domotic]

- home assistant
- raspberry
- <https://github.com/scipioni/home-assistant-example>

Install

- [example 1](#)
- pip3 install urllib3==1.20 -upgrade -target ~/.homeassistantdeps/ (telegram notify solved)

upgrade

```
pip install -U homeassistant
```

and after restart home assistant

with fabric

- <https://github.com/home-assistant/fabric-home-assistant>

hass

```
apt install python3 python3-venv incron mc
python3 -m venv ~/lib
. ~/lib/bin/activate
echo "source ~/lib/bin/activate" >> ~/.bashrc
pip install -U pip
pip install homeassistant
```

service

</etc/systemd/system/home-assistant.service>

```
[Unit]
Description=Home Assistant
After=network.target

[Service]
Type=simple
User=pi
ExecStart=/home/pi/lib/bin/hass -c "/home/pi"
```

```
[Install]
WantedBy=multi-user.target
```

enable service

```
systemctl daemon-reload
systemctl enable home-assistant
```

configuration example

```
sudo apt install git mc
git clone https://github.com/scipioni/home-assistant-example.git home-assistant-scipio
```

z-wave

/etc/udev/rules.d/local.conf

```
SUBSYSTEM=="tty", ACTION=="add", ATTRS{idVendor}=="0658",
ATTRS{idProduct}=="0200", SYMLINK+="zwave"
```

```
sudo apt install cython3 libudev-dev python3-sphinx python3-setuptools
```

```
. ~/lib/bin/activate
pip install cython
```

as normal user (no root)

```
. ~/lib/bin/activate
cd ~/
git clone --depth 1 https://github.com/OpenZWave/python-openzwave.git
cd python-openzwave
make build
make install
```

```
sudo apt install libmicrohttpd-dev
cd ~/
git clone --depth 1 https://github.com/OpenZWave/open-zwave-control-panel.git
cd open-zwave-control-panel/
# patch Makefile: see below
ln -s ~/lib/lib/python3.4/site-packages/libopenzwave-0.3.1-py3.4-linux-armv7l.egg/config
make
```

patch Makefile

```

--- Makefile.orig      2017-01-05 08:32:39.315501504 +0100
+++ Makefile       2017-01-05 08:33:38.385173320 +0100
@@ -21,7 +21,7 @@
CFLAGS := -c $(DEBUG_CFLAGS)
LDFLAGS := $(DEBUG_LDFLAGS)

-OPENZWAVE := ./open-zwave/
+OPENZWAVE := ./python-openzwave/openzwave/
LIBMICROHTTPD := -L/usr/local/lib/ -lmicrohttpd

INCLUDES := -I $(OPENZWAVE)/cpp/src -I
$(OPENZWAVE)/cpp/src/command_classes/ \
@@ -34,15 +34,15 @@
# for Linux uncomment out next three lines
LIBZWAVE := $(wildcard $(OPENZWAVE)/*.a)
-#LIBUSB := -ludev
-#LIBS := $(LIBZWAVE) $(GNUTLS) $(LIBMICROHTTPD) -pthread $(LIBUSB) -lresolv
+LIBUSB := -ludev
+LIBS := $(LIBZWAVE) $(GNUTLS) $(LIBMICROHTTPD) -pthread $(LIBUSB) -lresolv

# for Mac OS X comment out above 2 lines and uncomment next 5 lines
#ARCH := -arch i386 -arch x86_64
#CFLAGS += $(ARCH)
#LIBZWAVE := $(wildcard $(OPENZWAVE)/cpp/lib/mac/*.a)
-LIBUSB := -framework IOKit -framework CoreFoundation
-LIBS := $(LIBZWAVE) $(GNUTLS) $(LIBMICROHTTPD) -pthread $(LIBUSB) $(ARCH) -lresolv
+#LIBUSB := -framework IOKit -framework CoreFoundation
+LIBS := $(LIBZWAVE) $(GNUTLS) $(LIBMICROHTTPD) -pthread $(LIBUSB) $(ARCH) -lresolv

%.o : %.cpp
$(CXX) $(CFLAGS) $(INCLUDES) -o $@ $<

```

z-wave panel control

```

sudo systemctl stop home-assistant
cd ~/open-zwave-control-panel
./OZWcp -p 8888

```

open <http://pi:8888> and initialize /dev/ttyACM0

```

CTRL+C
sudo systemctl start home-assistant

```

reverse proxy

/etc/nginx/sites-enabled/homeassistant

```
server {  
    listen 80;  
    server_name "scipio.csgalileo.org";  
  
    # create this folder empty  
    location /.well-known/acme-challenge {  
        root /var/www;  
        allow all;  
    }  
  
    location / {  
        return 301 https://$server_name$request_uri;  
    }  
}  
  
server {  
    listen 443 ssl;  
    server_name "scipio.csgalileo.org";  
    ssl on;  
  
    proxy_buffering off;  
    location / {  
        proxy_pass http://localhost:8123/;  
        proxy_set_header Host $host;  
    }  
  
    ssl_certificate /etc/ssl/certs/scipio.csgalileo.org.cer;  
    ssl_certificate_key /etc/ssl/private/scipio.csgalileo.org.key;  
}
```

MQTT

```
apt install mosquitto
```

```
mosquitto_passwd /etc/mosquitto/pwfile scipio
```

zones

```
mosquitto_passwd /etc/mosquitto/pwfile simo
```

```
~/homeassistant/known_devices.yaml
```

github

setup

```
git config --global push.default simple
git clone https://github.com/scipioni/home-assistant.git
cd home-assistant
git remote add upstream https://github.com/home-assistant/home-assistant.git
git fetch -v

# script/setup
```

create a branch with expected work

```
git branch telegram-webhooks
git checkout telegram-webhooks
git push --set-upstream origin telegram-webhooks
```

everyday work on branch

```
...
git add
git commit
git push
```

rebase before pull request

```
git fetch upstream dev
git rebase upstream/dev

# in case of conflicts
... edit conflicts
git add ...
git rebase --continue

# -f is necessary (Git will reject it because there isn't a direct path from
# the commit on the server to the commit on your branch)
git push -f
```

now in github project “new pull request”

github docs

```
git clone https://github.com/scipioni/home-assistant.git
```

```
cd home-assistant.github.io.git
git remote add upstream https://github.com/home-assistant/home-assistant.github.io.git
git fetch -v

# script/setup
```

create a branch with expected work

```
git branch telegram-webhooks
git checkout telegram-webhooks
git push --set-upstream origin telegram-webhooks
```

ruby

```
sudo apt install y ruby ruby-dev
sudo gem install bundler
cd home-assistant.github.io.git
bundle
rake generate
```

test site

```
rake preview
```

everyday work on branch

```
...
git add
git commit
git push
```

rebase before pull request

```
git fetch upstream next
git rebase upstream/next

# in case of conflicts
... edit conflicts
git add ...
git rebase --continue

# -f is necessary (Git will reject it because there isn't a direct path from
# the commit on the server to the commit on your branch)
git push -f
```

now in github project “new pull request”

motion

Install latest release from <https://github.com/Motion-Project/motion>

[/etc/motion/motion.conf](#)

```
on_picture_save /usr/bin/motion-homeassistant %f
```

[/usr/bin/motion-homeassistant](#)

```
#!/bin/sh

F=$1
ln -sf $(basename $F) $(dirname $F)/lastsnap.jpg
```

[config.yaml](#)

```
camera:
  - platform: local_file
    name: soggiorno
    file_path: /media/usb0/photo/lastsnap.jpg
```

sensors

- /dev-service → zwave → set_config_parameter

disable LED on fibardo FGMS-001

```
{
"node_id": 3,
"parameter": 80,
"value": 0
}
```

Foscam IP camera

```
vlc rtsp://hass:password1@192.168.2.14:554/videoMain
```

automation

create a virtual switch

[input_boolean.yaml](#)

```
motion_detected:
  name: Motion rilevato
  initial: off
  icon: mdi:run
```

we can turn on this virtual switch with as web service

```
curl -X POST -H "x-ha-access: xxx" -H "Content-Type: application/json" -d
'{"state": "on"}' \
http://localhost:8123/api/states/input_boolean.motion_detected
```

automation that reset virtual switch after 2 seconds

[automation/on-motion.yaml](#)

```
alias: 'reset motion state'
trigger:
  platform: state
  entity_id: input_boolean.motion_detected
  to: 'on'
action:
  # after two seconds reset motion_detected state
  - delay: '00:00:02'
  - service: input_boolean.turn_off
    data:
      entity_id: input_boolean.motion_detected
```

camera motion

- <https://github.com/hokus15/home-assistant-config>

```
sudo apt install incron
```

as hass user edit incrontab 'incrontab -e' (incrontab -l to see)

```
/media/usb0/photo/C1_00626E611E80/snap/ IN_CLOSE_WRITE echo "$$ $$ $@ $$ % $"
```

From:
<https://wiki.csgalileo.org/> - Galileo Labs

Permanent link:
<https://wiki.csgalileo.org/projects/internetofthings/homeassistant?rev=1506148713>

Last update: **2017/09/23 08:38**

