

Requirements

HW: 2 nic device

OS: Ubuntu server 17.10

```
apt install bash debootstrap schroot syslinux nfs-kernel-server tftpd-hpa  
xorriso pigz zfsutils-linux
```

Optional config

```
apt install isc-dhcp-server
```

network config nano /etc/netplan/01-netcfg.yaml

```
# This file describes the network interfaces available on your system  
# For more information, see netplan(5).  
network:  
  version: 2  
  renderer: networkd  
  ethernets:  
    ens3:  
      dhcp4: no  
      addresses: [10.1.22.2/24]  
      gateway4: 192.168.122.1  
      nameservers:  
        addresses: [8.8.8.8,8.8.4.4]  
    ens4:  
      dhcp4: yes
```

```
netplan apply
```

Build livenet environment

Preparazione dell'ambiente zfs

```
zpool create livenet /dev/sdb
```

```
zfs create livenet/images
```

```
zfs create livenet/boot
```

Download package git clone <https://github.com/scipioni/livenet-server.git> edit /etc/default/livenet like this

```
# folder that contains livenet system
BASE=/livenet
IMAGES=${BASE}/images
BOOT=${BASE}/boot
```

Trivial FTP

edit /etc/default/tftp-hpa

```
TFTP_USERNAME="tftp"
TFTP_DIRECTORY="/zfsp_livenet/boot"
TFTP_ADDRESS="0.0.0.0:69"
TFTP_OPTIONS="--secure"
```

```
mkdir /livenet/boot/pxelinux.cfg
cp -a /usr/lib/syslinux/* /livenet/boot
cp /livenet/boot/modules/efi64/* /livenet/boot
```

edit /livenet/boot/pxelinux.cfg/default

```
default menu.c32
prompt 0
#timeout 100

menu title PXE Special Boot Menu
MENU AUTOBOOT Starting Livenet in # seconds

label bootlocal
    menu label ^Boot local disk
    menu default
    localboot 0

label nfs
    menu label Ubuntu 18.04 - diskless
    kernel /bionic/kernel
    append initrd=/bionic/initrd ro
livenet_root=10.1.22.2:/zfsp_livenet/images/bionic livenet_profile=default

label nfs
    menu label Ubuntu 14.04 - install
    kernel /trusty/kernel
    append initrd=/trusty/initrd ro livenet_root=10.0.254.240:/images/trusty
livenet_profile=default livenet_action=install livenet_action_end=reboot
```

BUILD IMAGE CLIENT

zfs create livenet/images/bionic debootstrap -arch amd64 bionic /zfsp_livenet/images/bionic/
<http://archive.ubuntu.com/ubuntu>

cd /livenet/images run

```
R=bionic
cat > ${R}/etc/hosts <<QWK
127.0.0.1    localhost livenet-host
::1        localhost ip6-localhost ip6-loopback
ff02::1     ip6-allnodes
ff02::2     ip6-allrouters
QWK

chroot ${R} lsb_release -c | awk '{print $2}' > ${R}/etc/debian_chroot
chroot bionic/
chroot ${R} apt-get -y -q install locales dialog
chroot ${R} locale-gen en_GB.UTF-8
chroot ${R} locale-gen it_IT.UTF-8
chroot ${R} update-locale LANG=it_IT.UTF-8 LANGUAGE=it:en_US:en
echo Europe/Rome > ${R}/etc/timezone
cp ${R}/usr/share/zoneinfo/Europe/Rome ${R}/etc/localtime
cat > ${R}/usr/sbin/policy-rc.d <<QWE
#!/bin/sh

# dpkg/apt not start any daemons when things are installed in the chroot

if [ ! "\\\`cat /etc/hostname\\\`" = "\\\`hostname\\\`" ]; then
    exit 101
fi
QWE

chmod +x ${R}/usr/sbin/policy-rc.d
```

```
mount --bind /zfsp_livenet/images/bionic/boot/ /zfsp_livenet/boot/bionic
```

```
DISTR=bionic

cat > /etc/apt/sources.list <<QWE
#####
##### OFFICIAL UBUNTU REPOS #####
#####
##### Ubuntu Main Repos
deb http://archive.ubuntu.com/ubuntu/ ${DISTR} main restricted universe
multiverse
##### Ubuntu Update Repos
deb http://archive.ubuntu.com/ubuntu/ ${DISTR}-security main restricted
universe multiverse
deb http://archive.ubuntu.com/ubuntu/ ${DISTR}-updates main restricted
```

```
universe multiverse
deb http://archive.ubuntu.com/ubuntu/ ${DISTR}-proposed main restricted
universe multiverse
deb http://archive.ubuntu.com/ubuntu/ ${DISTR}-backports main restricted
universe multiverse
##### Ubuntu Partner Repo
deb http://archive.canonical.com/ubuntu ${DISTR} partner
QWE
```

```
apt update apt -y upgrade
apt -y install initramfs-tools python-passlib pv screen byobu lsof pigz
rsync nfs-common libpam-script xloadimage contrack
```

install livenet client package

```
# copiare /home/scipio/.netrv e /home/scipio/.gitconfig in <chroot>/root/
cd /root
git clone https://github.com/scipioni/livenet-client.git
cd livenet-client
git checkout bionic
mv .git /
git status
find / -maxdepth 1 > .gitignore
```

inside git directory

```
rsync -avb etc/ /etc/
rsync -avb usr/ /usr/
rsync -avb debian /
rsync -avb README.md /
apt-get -y install linux-generic
```

etc/initramfs-tools/hooks/livenet

```
#!/bin/sh -e
# initramfs hook for livenet
#set -x
PREREQ=""

# Output pre-requisites
prereqs()
{
    echo "$PREREQ"
}

case "$1" in
    prereqs)
        prereqs
```

```
        exit 0
        ;;
esac

. /usr/share/initramfs-tools/hook-functions

rm ${DESTDIR}/bin/cpio # importante! altrimenti rimane un cpio troppo
semplificato
copy_exec /bin/cpio /bin

mkdir -p ${DESTDIR}/conf
cp /etc/livenet/livenet.conf ${DESTDIR}/conf
[ -f /etc/livenet/livenet.conf.override ] && cp
/etc/livenet/livenet.conf.override ${DESTDIR}/conf
cp /etc/initramfs-tools/scripts/functions-livenet ${DESTDIR}/conf

manual_add_modules aufs
manual_add_modules overlayfs
auto_add_modules net
auto_add_modules nfsv4

# pulizia di firmware non necessario e pesante
set +e
rm -f ${DESTDIR}/lib/firmware/* >/dev/null 2>&1
set -e

### qui sotto andrebbe commentato in produzione ###

# tastiera italiana in initram
# attivata da do_debug_shell (loadkeys /etc/boottime.kmap.gz)
#cp -au /etc/console-setup/cached.kmap.gz ${DESTDIR}/etc/boottime.kmap.gz

# nfs4
#copy_exec /usr/sbin/rpc.idmapd /bin
#copy_exec /sbin/mount.nfs /bin
#cp -au /etc/netconfig ${DESTDIR}/etc/netconfig

#cat > ${DESTDIR}/etc/passwd <<EOF
#nobody::65534:65534:nobody:/nonexistent:/bin/sh
#EOF
#cat > ${DESTDIR}/etc/group <<EOF
#nogroup:x:65534:
#EOF

# debug purpose #####
# ricordati di mettere FRAMEBUFFER=n in /etc/initramfs-tools/conf.d/splash
#copy_exec /sbin/ifconfig
#copy_exec /sbin/lsmmod /bin
#copy_exec /usr/bin/lspci /bin
#####
```

```
# wireless #####  
#copy_exec /sbin/iwconfig  
#copy_exec /sbin/iwlist  
#copy_exec /sbin/iwpriv  
#copy_exec /sbin/iwevent  
#copy_exec /sbin/iwgetid  
#copy_exec /sbin/iwspy  
#copy_exec /usr/sbin/rfkill  
#cp -au /lib/firmware/iwl*-[13].ucode ${DESTDIR}/lib/firmware  
#####
```

Rebuild initramfs image

In-mng -kernel

DHCP

Abilitare dhcpd su specifica scheda

Editare la riga in

/etc/default/isc-dhcp-server

```
INTERFACESv4="ens3"
```

Configurazione dhcpd

editare il file /etc/dhcp/dhcpd.conf al termine service isc-dhcp-service restart

```
ddns-update-style none;  
authoritative;  
  
option domain-name "livenet";  
option domain-name-servers 8.8.8.8;  
  
allow bootp;  
allow booting;  
  
option space PXE;  
# Code 1: Multicast IP address of bootfile  
option PXE.mtftp-ip code 1 = ip-address;  
# Code 2: UDP port that client should monitor for MTFTP responses  
option PXE.mtftp-cport code 2 = unsigned integer 16;  
# Code 3: UDP port that MTFTP servers are using to listen for MTFTP requests  
option PXE.mtftp-sport code 3 = unsigned integer 16;  
# Code 4: Number of secondes a client must listen for activity before trying
```

```
#          to start a new MTFTP transfer
option PXE.mtftp-tmout code 4 = unsigned integer 8;
option PXE.mtftp-delay code 5 = unsigned integer 8;
# Code 5: Number of secondes a client must listen before trying to restart
#          a MTFTP transfer
option PXE.discovery-control code 6 = unsigned integer 8;
option PXE.discovery-mcast-addr code 7 = ip-address;
set vendor-string = option vendor-class-identifier;

class "PXE" {
    match if substring(option vendor-class-identifier, 0, 9) = "PXEClient";
    option vendor-class-identifier "PXEClient";
    vendor-option-space PXE;
    option PXE.mtftp-ip 0.0.0.0;
}

class "Etherboot" {
    match if substring(option vendor-class-identifier, 0, 9) = "Etherboot";
    option vendor-class-identifier "Etherboot";
    vendor-option-space PXE;
    option PXE.mtftp-ip 0.0.0.0;
}

class "LIVENET" {
    match if (substring(option vendor-class-identifier,0,7) = "LIVENET") or
(substring(option vendor-class-identifier,0,9) = "PXEClient") or
(substring(option vendor-class-identifier,0,9) = "Etherboot");
    log ( info, "Packet from PXE or LIVENET client");
}

shared-network "clients" {
    subnet 10.1.22.0 netmask 255.255.255.0 {
        option subnet-mask 255.255.255.0;
        option routers 10.1.22.2;
        #default-lease-time 28800;
        #max-lease-time 86400;

        pool {
            # restringe il lease solo alla classe LIVENET
            allow members of "LIVENET";
            range 10.1.22.10 10.1.22.100;
            filename "/pxelinux.0";
            next-server 10.1.22.2;
        }
    }
}
```

From:
<https://wiki.csgalileo.org/> - **Galileo Labs**

Permanent link:
<https://wiki.csgalileo.org/projects/livenet/server>

Last update: **2018/03/21 11:56**

