

# docker

## install

### ubuntu

```
apt-get install -y ca-certificates curl gnupg lsb-release
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo gpg --
dearmor -o /usr/share/keyrings/docker-archive-keyring.gpg
echo "deb [arch=$(dpkg --print-architecture) signed-
by=/usr/share/keyrings/docker-archive-keyring.gpg]
https://download.docker.com/linux/ubuntu \
  $(lsb_release -cs) stable" | sudo tee
/etc/apt/sources.list.d/docker.list > /dev/null
apt update
apt-get install -y docker-ce docker-ce-cli containerd.io
mkdir /usr/local/lib/docker/cli-plugins -p
curl -SL
https://github.com/docker/compose/releases/download/v2.2.2/docker-compo
se-linux-x86_64 -o /usr/local/lib/docker/cli-plugins/docker-compose
chmod +x /usr/local/lib/docker/cli-plugins/docker-compose
```

run docker as user

```
usermod -aG docker hass
```

## deploy

get a docker-compose.yml file and edit it

create and run in background

```
docker-compose up -d
```

check

```
docker ps
docker stop <id>
```

autostart

```
docker update --restart unless-stopped <id>
```

apply changes on containers if change docker-compose.yml

```
docker-compose up -d --no-deps --build
```

## docker backup example

```
#!/bin/sh

CONTAINER=52e59999a02b
TARGET=/backup/
SOURCE=/var/lib/docker/volumes/geonode_3x1t-backup-restore/_data/

set -x
rm $SOURCE/2*
docker exec -it $CONTAINER python manage.py backup -f --
config=/usr/src/geonode_3x1t/geonode_3x1t/br/settings_docker.ini --backup-
dir=/backup_restore/
rsync -av $SOURCE $TARGET
```

## create image

- <https://dockerlabs.collabnix.com/beginners/building-your-first-alpine-container.html>

start from a base image, alpine for example

```
docker pull alpine

# create a new container on alpine image
docker run -dit alpine sh

# get container id
docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
3fdbad8aa816	alpine	"sh"	4 minutes ago	Up 4 minutes	
keen_black					

attach to container and copy directory from host to container

```
docker attach 3f
apk update
apk add nss
mkdir /opt
exit

docker cp /opt/sslvpn-plus 3f:/opt # this op stop container
docker start 3f
```

commit container 3f into image

```
docker commit 3f
```

tag image f8

```
docker tag f8 sslvpn-plus-leonardo
```

create container vpn-leonardo from image sslvpn-plus-leonardo

```
docker run --name vpn-leonardo --cap-add=NET_ADMIN --device=/dev/net/tun -dit sslvpn-plus-leonardo bash
```

## clone source

```
docker pull dryseawind/wildfly14jdk8
```

create Dockerfile

```
FROM dryseawind/wildfly14jdk8
MAINTAINER Stefano Scipioni
RUN /opt/jboss/wildfly-14.0.1.Final/bin/add-user.sh admin admin#password --silent
CMD ["/opt/jboss/wildfly-14.0.1.Final/bin/standalone.sh", "-c", "standalone.xml", "-b", "0.0.0.0", "-bmanagement", "0.0.0.0", "--debug"]
```

```
docker build -t "soes/wildfly:14" .
```

## rename volume

```
docker volume create --name <new_volume>
docker run --rm -it -v <old_volume>:/from -v <new_volume>:/to alpine ash -c "cd /from ; cp -av . /to"
docker volume rm <old_volume>
```

## docker registry (private)

create local image and tag with remote registry url

```
# get image from official docker registry
docker pull docker.io/hello-world

# tag
docker tag hello-world docker.csgalileo.org/hello-world
```

push

```
docker push docker.csgalileo.org/hello-world
```

## docker registry (public)

retag local builded image to remote image

[download](#)

```
docker tag galileo/trac:1.4.3 scipioit/trac:1.4.3
```

push to docker.io

[download](#)

```
docker push scipioit/trac:1.4.3
```

## docker swarm

- [docker routing mesh, SNAT](#)

init

```
docker swarm init --advertise-addr 185.91.188.93
```

convert web network scoped "local" to swarm scope

```
docker network rm web  
docker network create -d overlay web
```

deploy compose as swarm

```
cd ~/traefik  
docker stack deploy -c docker-compose.yml hosting3
```

add worker

```
# on manager get token  
docker swarm join-token worker  
  
# on worker add to manager  
docker swarm join --token xxxx 172.30.18.94:2377
```

```
# on manager check nodes
docker node ls
```

assign label to nodes

```
docker node ls
ID                               HOSTNAME     STATUS     AVAILABILITY     MANAGER
STATUS  ENGINE  VERSION
n4z6nb6c8xi6el63a6b0vflyv *    ujitsi-dev  Ready     Active            Leader
20.10.7
jen361j71yr6k96zrhx7x7b6a      ujitsireg3  Ready     Active
20.10.12

docker node update --label-add type=jibri jen361j71yr6k96zrhx7x7b6a
docker node update --label-add type=jvb n4z6nb6c8xi6el63a6b0vflyv
```

spread the deployment across nodes based on the value of "type" label: one node on type=jvb, one on type=jibri

```
docker service update --placement-pref-add 'spread=node.labels.type'
meet2_jibri
```

check spread

```
docker service ps meet2_jibri |grep Running
rbv77rkxpqlf    meet2_jibri.1      galileo/jibri:stable-6726-1    ujitsireg3
Running        Running 5 hours ago
jan7bs8ko2c0    meet2_jibri.2      galileo/jibri:stable-6726-1    ujitsi-dev
Running        Running 5 hours ago
```

add a constraint to other services (meet2jvb, meet2jicofo, ...) to run on specific node

```
docker service update --constraint-add 'node.labels.type == jvb' meet2_jvb
```

show docker services across nodes

```
docker stack ps meet2 |grep Runn
```

show node labels

```
docker node ls -q | xargs docker node inspect -f '{{ .ID }} [{{
.Description.Hostname }}]: {{ range $k, $v := .Spec.Labels }}{{ $k }}={{ $v
}} {{end}}'
```

From:

<https://wiki.csgalileo.org/> - **Galileo Labs**

Permanent link:

<https://wiki.csgalileo.org/projects/zibaldone/linux/docker?rev=1660725639>



Last update: **2022/08/17 10:40**