

# ansible

## basic op

```
ansible all --list-hosts
```

```
ansible all -m ping
```

## playbook

[helloworld.yaml](#)

```
- name: helloworld
  hosts: nodes
  tasks:
    - name: Ping my hosts
      ansible.builtin.ping:
    - name: Print message
      ansible.builtin.debug:
        msg: Hello world
```

```
ansible-playbook helloworld.yaml
```

[addkeys.yaml](#)

```
- name: Add ssh key to ubuntu user
  hosts: nodes
  tasks:
    - name: Set authorized key took from file
      authorized_key:
        user: ubuntu
        state: present
        key: "{{ lookup('file', '/root/.ssh/id_ed25519.pub') }}"
</file>

<code>
ansible-playbook addkeys.yaml
</code>

==== install ====

<code bash>
python3 -m pip install --user ansible
</code>
```

```
===== config =====  
  
<file ini /etc/ansible/hosts>  
[nodes]  
10.45.0.1  
10.45.0.2  
10.45.0.3  
10.45.0.4  
10.45.0.5
```

From:  
<https://wiki.csgalileo.org/> - Galileo Labs

Permanent link:  
<https://wiki.csgalileo.org/tips/ansible?rev=1662711761>

Last update: **2022/09/09 10:22**

