

OpenHAB2

- <https://mysmarthomeweb.wordpress.com>

Install

device USB container

```
lxc config device add openhab2 rfxcom unix-char path=/dev/ttyACM0
lxc config device set openhab2 rfxcom mode 666
```

</etc/apt/sources.list.d/openhab2.list>

```
cat > /etc/apt/sources.list.d/openhab2.list <<EOF
deb [trusted=yes]
https://openhab.ci.cloudbees.com/job/openHAB-Distribution/ws/distributi
ons/openhab-offline/target/apt-repo/ /
deb [trusted=yes]
https://openhab.ci.cloudbees.com/job/openHAB-Distribution/ws/distributi
ons/openhab-online/target/apt-repo/ /
EOF
```

```
wget -q0 - 'http://www.openhab.org/keys/public-key-snapshots.asc' | sudo
apt-key add -
sudo apt update
apt install openjdk-8-jre
```

```
apt install openhab2-online
```

```
sudo systemctl enable openhab2.service
sudo systemctl start openhab2.service
sudo systemctl status openhab2.service
```

WEB GUI

- <http://localhost:8080>

CLI

```
/usr/share/openhab2/runtime/karaf/bin/client
```

Manage configuration

```
config:list "(service.pid=org.openhab.addons)"
```

change params

```
config:property-set -p org.openhab.addons legacy true
config:property-set -p org.openhab.addons remote true
config:property-set -p org.openhab.addons experimental true
```

Install features

show features

```
feature:list | grep network
```

interesting features

```
feature:install openhab-runtime-compat1x

feature:install openhab-transformation-regex
feature:install openhab-binding-exec
feature:install openhab-persistence-rrd4j

feature:install openhab-ui-habmin
feature:install openhab-ui-habanel

feature:install openhab-action-telegram

feature:install openhab-binding-network
# feature:install openhab-binding-lgtv
```

Introspection

```
openhab> things list
yahooweather:weather:158197f6007 (Type=Thing, Status=ONLINE, Label=Weather
Information, Bridge=null)

openhab> items list
yahooweather_weather_158197f6007_temperature (Type=NumberItem, State=2,
Label=Temperature, Category=Temperature)
yahooweather_weather_158197f6007_humidity (Type=NumberItem, State=77,
Label=Humidity, Category=Humidity)
yahooweather_weather_158197f6007_pressure (Type=NumberItem, State=30308.19,
Label=Pressure, Category=Pressure)

openhab> links list
```

```
yahooweather_weather_158197f6007_temperature ->  
yahooweather:weather:158197f6007:temperature  
yahooweather_weather_158197f6007_humidity ->  
yahooweather:weather:158197f6007:humidity  
yahooweather_weather_158197f6007_pressure ->  
yahooweather:weather:158197f6007:pressure
```

Log

console

```
# change log level  
log:set DEBUG  
  
# clear  
log:clear  
  
# show continuous tail  
log:tail
```

Persistence

Enable rrd4j binding

</etc/openhab2/services/rrd4j.cfg>

```
ctr5min.def=COUNTER,900,0,U,300  
ctr5min.archives=AVERAGE,0.5,1,365:AVERAGE,0.5,7,300  
#  
ctr5min.items=systeminfo_computer_15819c96492_cpu_load,yahooweather_weather_158197f6007_temperature,yahooweather_weather_158197f6007_humidity,yahooweather_weather_158197f6007_pressure
```

</etc/openhab2/persistence/rrd4j.persist>

```
// persistence strategies have a name and a definition and are referred  
to in the "Items" section  
Strategies {  
    everyHour : "0 0 * * * ?"  
    everyDay  : "0 0 0 * * ?"  
  
    // if no strategy is specified for an item entry below, the default  
    list will be used  
    default = everyChange  
}  
  
/*
```

```

* Each line in this section defines for which item(s) which
strategy(ies) should be applied.
* You can list single items, use "*" for all items or "groupitem*" for
all members of a group
* item (excl. the group item itself).
*/
Items {
    // persist all items once a day and on every change and restore
them from the db at startup
    * : strategy = everyChange, everyDay, restoreOnStartup

    // additionally, persist all temperature and weather values every
hour
    Temperature*, Weather* : strategy = everyHour
}

```

demo mode

</etc/openhab2/services/addons.cfg>

```
package = demo
```

Programming

items

<items/cpu.items>

```

// create an item from another channel item "items list"
Number Cpu "Cpu [%.0f]" (signal) {
channel="systeminfo:computer:15819c96492:cpu#load" }

// fetch data from script every 2 seconds (install exec binding and
regex transformation)
Number TestLoad "Test load [%.0f]" (signal) {
exec="<[/etc/openhab2/test.sh:1000:REGEX((.*?))]"

```

<rules/cpu.rules>

```

import org.openhab.core.library.types.*
import org.openhab.core.persistence.*
import org.openhab.model.script.actions.*

```

```
val Timer timer = null
val Timer waitTimer = null
val int sleepMinutes = 1

rule "CPU too high"
when
    Item Cpu changed
then
    if (Cpu.state > 40) {
        if (timer == null) {
            // watch cpu for 5 seconds
            timer = createTimer(now.plusSeconds(5)) [|
                val message = "CPU troppo alta: " + Cpu.state.toString() + ".
Prossimo messaggio in "+ sleepMinutes.toString() + " minuti"
                sendTelegram("bot1", message)
                logWarn("home", message)

                waitTimer = createTimer(now.plusMinutes(sleepMinutes)) [|
                    timer = null
                    sleepMinutes = sleepMinutes*2
                ]
            ]
        }
    } else {
        if(timer != null) {
            timer.cancel
            timer = null
            sleepMinutes = 1
        }
    }
end
```

From:

<https://wiki.csgalileo.org/> - **Galileo Labs**

Permanent link:

<https://wiki.csgalileo.org/tips/openhab2?rev=1478169030>

Last update: **2016/11/03 11:30**

