

Pulsar

```
wget
https://archive.apache.org/dist/pulsar/pulsar-2.4.1/apache-pulsar-2.4.1-bin.
tar.gz
tar xvfz apache-pulsar-2.4.1-bin.tar.gz
cd apache-pulsar-2.4.1

# connectors

# storage
wget
https://archive.apache.org/dist/pulsar/pulsar-2.4.1/apache-pulsar-offloaders
-2.4.1-bin.tar.gz
tar xvfz apache-pulsar-offloaders-2.4.1-bin.tar.gz
mv apache-pulsar-offloaders-2.4.1/offloaders offloaders
```

storage s3

conf/broker.conf

```
...
managedLedgerOffloadDriver=S3
s3ManagedLedgerOffloadBucket=pulsar-topic-offload
s3ManagedLedgerOffloadServiceEndpoint=http://127.0.0.1:9000
...
```

```
conf/pulsarenv.sh export AWSACCESSKEYID=ABC123456789 export
AWSSECRETACCESS_KEY=ded7db27a4558e2ea8bbf0bf37ae0e8521618f366c
```

run

```
bin/pulsar standalone
```

define a storage threshold in “public” tenant, default name space

```
bin/pulsar-admin namespaces set-offload-threshold --size 0 public/default
```

From:
<https://wiki.csgalileo.org/> - **Galileo Labs**

Permanent link:
<https://wiki.csgalileo.org/tips/pulsar?rev=1569244285>

Last update: **2019/09/23 15:11**



