

[zfs, libvirt]

ZFS

```
apt install zfsutils-linux
```

```
sudo zfs list
```

create filesystem 'lab' on 'LXD' pool

```
sudo zfs create LXD/lab  
sudo zfs set mountpoint=/lab LXD/lab
```

```
sudo zfs destroy LXD/lab
```

create pool

Pool can be created on disk or partition. In case of partition this is an example

Number	Start (sector)	End (sector)	Size	Code	Name
1	1026048	74426367	35.0 GiB	8300	Linux filesystem
2	2048	1026047	500.0 MiB	EF02	
3	74426368	76474367	1000.0 MiB	8200	
4	76474368	976756735	429.3 GiB	BF01	# <----- zfs
5	976756736	976773119	8.0 MiB	BF07	# ???

```
zpool create lxd /dev/sda4
```

docker

```
systemctl stop docker  
rm -fR /var/lib/docker  
zfs create -o mountpoint=/var/lib/docker rpool/docker-root  
zfs create -o mountpoint=/var/lib/docker/volumes rpool/docker-volumes  
systemctl start docker
```

/etc/docker/daemon.json

```
{  
  "default-address-pools":  
  [  
    {"base": "172.16.0.0/21", "size": 26}  
  ],  
  "storage-driver": "zfs",  
  "features": {
```

```
"buildkit" : true
}
}
```

libvirt

add ZFS pool to libvirt

```
# in bionic
apt install libvirt-daemon-driver-storage-zfs && systemctl restart libvirtd

# create zfs filesystem
zfs create rpool/libvirt

virsh pool-define-as --name zfspool --source-name rpool/libvirt --type zfs
virsh pool-start zfspool
virsh pool-autostart zfspool
```

create volume (not possible in virt-manager)

```
virsh vol-create-as --pool zfspool --name maas2 --capacity 10G
```

destroy volume

```
virsh vol-delete --pool zfspool maas2
```

add volume to instance

create file mydevice.xml

```
<disk type='block' device='disk'>
  <driver name='qemu' type='raw' cache='none' />
  <source dev='/dev/zvol/rpool/libvirt/juju-controller' />
  <target dev='vda' bus='virtio' />
</disk>
```

add volume

```
virsh attach-device --config juju-controller mydevice.xml
```

virtualbox

create volume

```
zfs create -V 50G rpool/win7
```

create vmdk file that point /dev/zvol/rpool/win7 (/opt/vms/win7.vmdk keeps little)

```
VBoxManage internalcommands createrawvmdk -filename /opt/vms/win7.vmdk -  
rawdisk /dev/zvol/rpool/win7
```

now use /opt/vms/win7.vmdk file as virtual hard disk for virtualbox guest

tuning

pool on SSD <https://storagetuning.wordpress.com/2011/12/01/zfs-tuning-for-ssds/>

[/etc/systctl.conf](#)

```
vfs.zfs.l2arc_noprefetch=0
```

zfs root from live system

```
zpool export rpool  
zpool import -R /mnt rpool  
  
umount everything inside /mnt  
  
zfs mount rpool/ROOT/ubuntu  
  
zfs set devices=off rpool  
mount --rbind /dev /mnt/dev  
mount --rbind /proc /mnt/proc  
mount --rbind /sys /mnt/sys  
chroot /mnt /bin/bash --login  
  
... work here  
  
exit  
mount | grep -v zfs | tac | awk '/\/mnt/ {print $3}' | xargs -i{} umount -lf  
{}  
zpool export rpool  
reboot
```

remote replication

in origin make a snapshot of volume

```
zfs snap storage/cimateriali@snap1
```

destination volume cannot be exists

```
zfs send -R storage/cimateriali@snap1 | pv | ssh zfs1 zfs recv -F -u
rpool/cimateriali
# zfs destroy storage/cimateriali@snap1
```

on destination destroy snapshot to have volume

```
zfs destroy rpool/cimateriali@snap1

# volsize ?
zfs get volsize,reservation rpool/cimateriali
zfs set volsize=20G rpool/cimateriali
zfs get volsize,reservation rpool/cimateriali
```

syncoid

- <https://github.com/jimsalterjrs/sanoid>

```
apt install pv lzop mbuffer
wget https://raw.githubusercontent.com/jimsalterjrs/sanoid/master/syncoid -O
/usr/local/bin/syncoid
chmod +x /usr/local/bin/syncoid
```

using from server zfs1 (to server zfs2)

```
syncoid rpool/share-os root@zfs2:rpool/share-os
```

incremental backup

consider a FS rpool/test

```
FS=rpool/test

# make a first snapshot
zfs snapshot rpool/test@snap01
```

if files are added to FS used space of FS grow

```
sync && zfs list -t all -r $FS
GROW --->rpool/test      200M   138G   200M  /test
        rpool/test@01    64K    -      100M  -
```

if files are changed in FS used space of SNAP grow

```
sync && zfs list -t all -r $FS
        rpool/test      200M   138G   200M  /test
```

```
GROW --->rpool/test@01 100M - 100M -
```

---> CRYPTOLOCKER grows SNAP

check crypto locker every day

```
LIMIT_MB=100
FS=rpool/test

USED=$(zfs get -Hp used $FS@01 | cut -f3)
if [ $USED -gt $((LIMIT_MB*1000*1000)) ]; then
    echo "CRYPTOLOCKER detected"
fi
```

swap

```
zfs create -V 4G -b $(getconf PAGESIZE) -o compression=zle \
-o logbias=throughput -o sync=always \
-o primarycache=metadata -o secondarycache=none \
-o com.sun:auto-snapshot=false rpool/swap
```

```
mkswap -f /dev/zvol/rpool/swap
```

```
echo /dev/zvol/rpool/swap none swap defaults 0 0 >> /etc/fstab
swapon -av
```

From:
<https://wiki.csgalileo.org/> - Galileo Labs

Permanent link:
<https://wiki.csgalileo.org/tips/zfs>

Last update: **2023/01/18 11:22**

