

[zfs, libvirt]

ZFS

```
apt install zfsutils-linux
```

```
sudo zfs list
```

create filesystem 'lab' on 'LXD' pool

```
sudo zfs create LXD/lab  
sudo zfs set mountpoint=/lab LXD/lab
```

```
sudo zfs destroy LXD/lab
```

create pool

Pool can be created on disk or partition. In case of partition this is an example

Number	Start (sector)	End (sector)	Size	Code	Name
1	1026048	74426367	35.0 GiB	8300	Linux filesystem
2	2048	1026047	500.0 MiB	EF02	
3	74426368	76474367	1000.0 MiB	8200	
4	76474368	976756735	429.3 GiB	BF01	# <----- zfs
5	976756736	976773119	8.0 MiB	BF07	# ???

```
zpool create lxd /dev/sda4
```

libvirt

add ZFS pool to libvirt

```
# create zfs filesystem  
zfs create rpool/libvirt  
  
virsh pool-define-as --name zfspool --source-name rpool --type zfs  
virsh pool-start zfspool  
virsh pool-autostart zfspool
```

create volume (not possible in virt-manager)

```
virsh vol-create-as --pool zfspool --name maas2 --capacity 10G
```

destroy volume

```
virsh vol-delete --pool zfspool maas2
```

virtualbox

create volume

```
zfs create -V 50G rpool/win7
```

create vmdk file that point /dev/zvol/rpool/win7 (/opt/vms/win7.vmdk keeps little)

```
VBoxManage internalcommands createrawvmdk -filename /opt/vms/win7.vmdk -  
rawdisk /dev/zvol/rpool/win7
```

tuning

pool on SSD <https://storagetuning.wordpress.com/2011/12/01/zfs-tuning-for-ssds/>

[/etc/sysctl.conf](#)

```
vfs.zfs.l2arc_noprefetch=0
```

zfs root from live system

```
zpool export rpool  
zpool import -R /mnt rpool
```

umount everything inside /mnt

```
zfs mount rpool/ROOT/ubuntu
```

```
zfs set devices=off rpool  
mount --rbind /dev /mnt/dev  
mount --rbind /proc /mnt/proc  
mount --rbind /sys /mnt/sys  
chroot /mnt /bin/bash --login
```

... work here

exit

```
mount | grep -v zfs | tac | awk '/\/mnt/ {print $3}' | xargs -i{} umount -lf  
{}  
zpool export rpool
```

```
reboot
```

remote replication

in origin make a snapshot of volume

```
zfs snap storage/cimateriali@snap1
```

destination volume cannot be exists

```
zfs snap storage/cimateriali@snap1
zfs send -R storage/cimateriali@snap1 | pv | ssh zfs1 zfs recv -F -u
rpool/cimateriali
# zfs destroy storage/cimateriali@snap1
```

on destination destroy snapshot to have volume

```
zfs destroy rpool/cimateriali@snap1

# volsize ?
zfs get volsize,reservation rpool/cimateriali
zfs set volsize=20G rpool/cimateriali
zfs get volsize,reservation rpool/cimateriali
```

incremental backup

consider a FS rpool/test

```
FS=rpool/test

# make a first snapshot
zfs snapshot rpool/test@snap01
```

if files are added to FS used space of FS grow

```
sync && zfs list -t all -r $FS
GROW --->rpool/test      200M   138G   200M  /test
        rpool/test@01   64K    -     100M  -
```

if files are changed in FS used space of SNAP grow

```
sync && zfs list -t all -r $FS
        rpool/test      200M   138G   200M  /test
GROW --->rpool/test@01  100M    -     100M  -
```

==> CRYPTOLOCKER grows SNAP

check crypto locker every day

```
LIMIT_MB=100
FS=rpool/test

USED=$(zfs get -Hp used $FS@01 | cut -f3)
if [ $USED -gt $(( $LIMIT_MB*1000*1000 )) ]; then
    echo "CRYPTOLOCKER detected"
fi
```

From:
<https://wiki.csgalileo.org/> - Galileo Labs

Permanent link:
<https://wiki.csgalileo.org/tips/zfs?rev=1504168567>

Last update: **2017/08/31 10:36**

